

Interactive displays are great for team meetings
/This is Why we make BIG PAD - designed for sharing.

BIG PAD

SMOOTH,
INTUITIVE
AND MADE FOR
SHARING



Sharp's 70" and 60" BIG PAD touchscreen LCD monitors are designed for smooth and effortless communication in a wide range of contexts. Their highly responsive touch pens allow several people to write on the same screen at the same time. And SHARP's Display Connect enables multifaceted wireless communication. Whether in the boardroom or the classroom, Sharp changes the way you communicate.




Simultaneous Writing

Recognising up to 10 points of contact, the PN-70TB3 and PN-60TB3 multi-touch LCD monitors allow up to four people to write on the screen at the same time using touch pens or fingers. Participants can take an active part in meetings, brainstorming sessions, classroom interactions, and more. Discussions and presentations become platforms for effective and lively exchanges of opinions.

Smooth, Highly Responsive Touch Pen

The professional passive touch pen without function buttons, shipped with BIG PAD, is so smooth and light that using it is like writing on paper. An optional dedicated touch pen with function buttons*1 also offers a pressure sensor at the tip of this slim and lightweight pen, which lets you write with high precision and with an effortless and uninterrupted flow.

ACTIVE TOUCH PEN (OPTIONAL)



PASSIVE TOUCH PEN (STANDARD)


User-Friendly SHARP Pen Software

Using a touch pen, you can easily launch and display the SHARP Pen Software user interface - a menu comprising smartly arranged icons that provide easy access to pen settings and functions. Each touch pen has its own dedicated menu, which can be displayed even when up to four people are writing on the screen at the same time. Pen settings such as colour and line thickness can be set and saved for each touch pen (with function buttons).



Handwriting Recognition


These interactive displays feature a handwriting recognition*3 function for converting selected onscreen handwriting into standard text. This convenient function allows you to utilize onscreen content to make neat and legible minutes of your meetings.



Work Smarter with SHARP Display Connect

SHARP Display Connect*4 supports effective and multifaceted communication. Onscreen content - including handwritten notes and drawings made in real time - can be viewed simultaneously on the BIG PAD and mobile devices*5 such as PCs, tablets, and smartphones. SHARP Display Connect facilitates interactive presentations, lively discussions, and paperless meetings in both business and educational scenes.

- SHARP Display Connect enables the following interactive functions on BIG PAD and mobile devices connected via wireless LAN:
 - sharing of onscreen content
 - transfer of files
 - interactive onscreen writing and drawing
 - remote control of the BIG PAD from mobile devices
- Up to 50 mobile devices*4*6 can be connected simultaneously.
- Files can be exchanged between mobile devices even if they are not connected to the BIG PAD.
- Users can capture onscreen images and save them on their mobile devices to make personally annotated memos (personal memo).
- SHARP Display Connect also connects two BIG PADs on the same local area network to enable larger-scale interactive communications.



*1 Optional for PN-70TB3/60TB3

*2 Bundled with PN-70TB3/60TB3

*3 Works with languages supported by SHARP Pen Software.

*4 Number of connectable mobile devices depends on the following condition:

- PN-70TB3/PN-60TB3 used with bundled software CD-ROM: Max. 50

*5 OS requirements: PCs: Windows® 7, Windows 8/8.1; Tablets: Windows 7, Windows 8/8.1, Android, iOS; Smartphones: Android, iOS

*6 Connecting 20 or more mobile devices requires at least two LAN access points. Software requires appropriate network and device configuration to run correctly

Sharp's Fastbox PC - Built for Purpose (Option)

The Fastbox PC purpose built for Sharp offers a compact, powerful and highly integrated single board computer with Intel Core i5 processor. Pre-installed with Sharp software applications and a high end graphics card, the device offers businesses a complete "Plug & Go" solution. The Fastbox PC is the perfect choice for mounting a PC on the back side of a BIG PAD interactive touch display.



Peerless Stand Solution for Sharp (Option)



The Peerless Mobile Stand offers the most complete flexible mobile solution for Sharp's Interactive Display. Designed exclusively for Sharp's IFPDs the durable 4" (102mm) swivel wheels provide easy mobility over various floor surfaces and through doorways. Once in place the two locking wheels ensure complete stability. The Peerless Stand can also be adjusted to suite your desired tilt and height.

MADE FOR SHARP



Touch-Operated Onscreen Display

Pressing the Touch Menu button displays an onscreen menu that lets you easily switch input sources, change volume level, or turn the touchscreen function on and off without using a remote controller.



Front-Mounted Speakers


Two speakers (10 W + 10 W) are mounted low on the front of the LCD monitor to deliver clearer sound.

Minimise Glare and Fingerprints

Protecting the screen is an anti-glare film that works to reduce glare and reflections and minimise fingerprint soiling on the glass.

MFP Connectivity


Documents and images scanned from a colour-scan-capable Sharp MFP can be imported directly to the pen software for display on the BIG PAD. For added convenience, image data shown onscreen - including notations - can be saved to a PC or sent directly to an MFP for printout.




A Wealth of Input/Output Terminals

The enhanced BIG PAD comes equipped with a wealth of input/output terminals - on the side and the bottom of the monitor - to enable easy connection with a wide variety of equipment. This array of terminals includes three HDMI ports, two D-sub ports, two DisplayPort™ terminals (one input, one output), and two touchscreen-supporting USB ports. One of the USB ports can be assigned to a regularly connected PC, such as a host PC used to operate the LCD monitor. The other USB port facilitates temporary connection to another PC, such as one used by a meeting participant. This allows easy PC connection without the need to switch the USB cable.

(Side)



(Bottom)




* For connecting keyboard, mouse, or USB flash drive.

Specifications

Model		PN-70TB3	PN-60TB3
Installation		Landscape	
		70-inch-class (69 1/2-inch [176.6 cm] diagonal) UV ² A*1 LCD	60-inch-class (60 1/16-inch [152.5 cm] diagonal) UV ² A*1 LCD
LCD Panel	Max. Resolution	1,920 x 1,080 pixels	
	Max. Display Colours (approx.)	1.06 billion colours	
	Pixel Pitch (H x V)	0.802 x 0.802 mm	0.692 x 0.692 mm
	Max. Brightness (average)*2	300 cd/m ²	
	Contrast Ratio	3,000 : 1	
	Viewing Angle (H/V)	160°/160° (CR≥10)	
	Active Screen Area (W x H) (approx.)	1,538.9 x 865.6 mm (60 9/16" x 34 1/16")	1,329.1 x 747.6 mm (52 3/16" x 29 7/16")
Response Time		6 ms (grey to grey, avg.)	
Backlight		LED, edge lit	
Touchscreen	Touch Technology	IR (infrared blocking detection method)	
	PC Connection Port	USB 2.0 (type B) x 2	
	Power Supply	Supplied from main unit	
	Multi Touch	10 points	
Protection Glass		Thickness: Approx. 3.4 mm*3 Shock resistance: 130 cm*4	Thickness: Approx. 3.0 mm*3 Shock resistance: 130 cm*4
Computer Input	Video	Analogue RGB (0.7 Vp-p) [75Ω], DisplayPort 1.1a	
	Synchronisation	Horizontal/vertical separation (TTL: positive/negative), Sync on green (D-sub 15-pin only), Composite sync (TTL: positive/negative)	
	Plug & Play	VESA DDC2B	
	Power Management	VESA DPMS	
Video Colour System		NTSC (3.58 MHz, 4.43 MHz), PAL, PAL60, SECAM	
Input Terminals*5		PC analogue: Mini D-sub 15-pin x 2*6, HDMI (HDCP and 1080p compatible, PC/AV signal compatible) x 3, 3.5 mm-diameter mini stereo jack x 2, Video x 1*6, Component video x 1*6, DisplayPort (HDCP compatible, PC signal compatible) x 1	
Output Terminals*5		3.5 mm-diameter mini stereo jack x 1, DisplayPort (HDCP compatible) x 1	
Input/Output Terminals*5		LAN port (10Base-T/100Base-TX) x 1	
Speaker Output	Built-in	10 W + 10 W	
	External	10 W + 10 W (6Ω)	
Mounting		VESA (4 points), 400 x 200 mm pitch, M6 screw	
Power Supply		100V – 240V AC, 50/60 Hz	
Power Consumption		225 W	185 W
Environmental Conditions	Operating Temperature	5°C to 35°C	
	Operating Humidity	20% to 80% RH (no condensation)	
Dimensions (W x D x H) (approx.)		1,647 x 94 x 1,010 mm (64 13/16" x 3 11/16" x 39 3/4")	1,437 x 94 x 890 mm (56 9/16" x 3 11/16" x 35")
Weight (approx.)		59 kg (130.1 lbs)	46 kg (101.5 lbs)
Main Accessories		AC power cord, remote control unit, batteries (AA size x 2), set-up manual, blank sticker, cable clamps x 5, camera mount, USB cable (3.0 m), eraser, pen tray PN-ZL02 Passive Touch Pen (without function button), SHARP Display Connect CD-ROM	

Dimensions



Windows® PC System Requirements

PC	PC/AT compatible machine with USB 2.0 port and screen resolution of 1,920 x 1,080 (CD-ROM drive required for installation)
CPU	Intel® Celeron® 1.6GHz, or AMD Sempron™ 1.6GHz or higher (Intel® Core™ 2 Duo 2.8GHz, or AMD Athlon™ II x 2 2.8 GHz or higher recommended)
OS	Windows® 7 (32-bit/64-bit), Windows® 8 (32-bit/64-bit), Windows® 8.1 (32-bit/64-bit)
Memory	2GB or more
Hard disk	200MB or more free space (additional space required for saving data)

Options

PN-ZL01: Active Touch Pen and Touch Pen adapter



Notes

*1 UV²A stands for Ultraviolet-induced Multi-domain Vertical Alignment, a photo-alignment technology that ensures uniform alignment of liquid crystal molecules. *2 Brightness depends on input mode and other picture settings. Brightness level will decrease slightly over the lifetime of the product. Due to the physical limitations of the equipment, it is not possible to maintain a precisely constant level of brightness. *3 Including AG film on the front and AR film on the back. *4 Approximate distance at which the glass panel can withstand the impact of a 500-gram iron ball dropped on its center. *5 Use a commercially available connection cable for PC and other video connections. *6 Analogue PC, video, and component video are switchable (on bottom interface); use the menu to select. Video and component video connections require conversion cable via mini D-sub 15-pin jack. *7 For connecting keyboard, mouse, and USB memory device.

Design and specifications are subject to change without prior notice. Windows is either a registered trademark or trademark of Microsoft Corporation in the US and/or other countries. DisplayPort and the DisplayPort Compliance Logo are trademarks owned by the Video Electronics Standards Association in the US and other countries. The terms HDMI and High-Definition Multimedia Interface and the HDMI logo are trademarks or registered trademarks of HDMI Licensing, LLC in the US and other countries. Intel, Intel Core, and Celeron are trademarks of Intel Corporation in the US and/or other countries. Sempron and Athlon are trademarks of Advanced Micro Devices, Inc. All other brand names and product names may be trademarks or registered trademarks of their respective owners. All trademarks acknowledged. E&OE. © Sharp Corporation July 2016. Ref: 17498 Sharp BIG PAD.

SHARP

Inspiring ideas from technology

www.sharp.co.uk

SHARP BUSINESS SYSTEMS UK PLC
4 FURZEGROUND WAY
STOCKLEY PARK, UXBRIDGE
MIDDLESEX, UB11 1EZ

TEL: +44 (0)20 8734 2000

